



## Material Technical Data Sheet

### SE Mica 40

Coarse-grained muscovite mica effect pigment used for architectural and surface coating applications. This grades large delaminated flakes of mica impact high luster and visibility due to the larger partial size.

|                      |                  |
|----------------------|------------------|
| Stucco               | Foundry Coatings |
| Asphalt Coatings     | Plastics         |
| Asbestos Replacement | Rubber           |
| Mold Releases        | Cultured Stone   |

### Typical Properties

|                        |             |
|------------------------|-------------|
| Sieve Analysis         | % retained  |
| +10 mesh               | <5.0%       |
| +40 mesh               | >90%        |
| Bulk Density (Colgate) | <38         |
| LOI (1000°C)           | <1.0%       |
| Color                  | Silver/Gray |
| Specific Gravity       | 2.82        |
| pH                     | 6.0-7.5     |
| CAS No.                | 12001-26-2  |

*\* Note: Specification & Chemical analysis can be furnished only when we get to know the grades / application desired by you.*

**Admin office:** 110 A Block City Center, Nr Idgah Circle Asarwa Bridge, Asarwa, Ahmedabad Gujarat 380 016 **INDIA Plant:** Plot No. 410 Phase II, Vatva G. I. D. C. Industrial Estate, Vatva, Ahmedabad Gujarat 382 445 **INDIA**  
E: [inquiry@gmciltd.com](mailto:inquiry@gmciltd.com) W: [www.gmciltd.com](http://www.gmciltd.com) T: +91 79905 25617 F: +91 79848 07644  
Certificate of Incorporation: U24290GJ2019PTC108256 GST NO.: 24AAHCG8288L1ZY

**GLOBAL METRO CHEM INDUSTRIES**